

The ISCO logo features the word "ISCO" in a bold, white, sans-serif font, with a white curved line above it that arches over the letters.

# FAST FLANGE

U.S. PATENT NO. 10,753,518



## PRODUCT OVERVIEW

Specifically designed for landfill applications, ISCO's Fast Flange delivers operations professionals an efficient and cost-effective solution for routine maintenance of landfill pipe systems.

Our easy to use and install Fast Flange is simple enough for one person to operate. Its innovative design allows for on-site retro fitting, seals for compliance, reduces hardware loss, and provides quick convenient access to internal pipe components. This ensures a responsive solution that elevates routine quality maintenance.





## PRODUCT HIGHLIGHTS

- Components made with corrosion-resistant materials and hardware—UV stabilized HDPE, 18-8 grade stainless steel or better.
- Available in, 6-, 8-, 12-, 18- and 24-inch diameter.
- The hinged lid allows for easy access while still connected to riser.
- Winged bolts are easy to tighten/loosen by hand.
- All hardware is captive. No risk of dropping or losing pieces when opening or closing lid.
- Sealed lid minimizes intrusion of ambient air when vacuum is applied.
- Testing data demonstrates less than 2 psi positive air pressure and 143-inch W.C. vacuum for minimum duration of 15 minutes, each test.
- Lid system seal consists of at least ¼-inch thick nitrile rubber gasket, O-ring or a similar material.
- Attached back-up ring is split for easy replacement.

